

INFRARED DOOR SECURITY DETECTOR

"L Type Casement Installation" 32 Photodiodes

917-K



- 3 meter detector / detection distance
- "L" type body
- 32 photo diodes
- 32ms Fast response speed
- Audible warning system
- Low power consumption
- Easy installation
- Long LED light lifetime
- IP54 Protection Class

ATEK 917 series door security detectors can read from 3 meters distance. With 32 built-in photodiodes with fast response speed, they provide fast security. There is external power unit working with 220VAC power supply.

The most important feature of the product is the audible alert notification, so that if the TX and RX units do not see each other within 15 seconds during the installation, they will make audible notification. Due to distinctive body designs, they can be used in door and security applications.

Due to high mounting tolerance, the TX, RX units can be easily connected to each other.

Technicial Specifications	
Response Time	61ms relay output 37ms transistor output
Number of Infra Red Diodes	32 units
Beam Scanning	128-94 Beam
Detection height	20 – 1840 mm
Infra Red Diode Distance	58.8mm
Power consumption	4W or 100mA @ 24VDC
Operating Temperature	-20°C +65°C
Mounting Tolerance	Up / Down: ± 10mm / 7 ° Forward / Reverse: ± 3mm / 5 °
Mechanical Measurements	2000mm x 28 mm x 10 mm
Infra Red Led Light Life	≤100000 Lux
Measuring Distance	3 meter
Protection Class	IP54 for TX and RX units, IP31 for power unit
Audible Warning	Buzzer integrated in RX unit

LED STATUS BOARD









Green LED



Red LED Status indicator Receiver unit





Green LED
Power indicator
Power Unit





Red LED
Status indicator
Power Unit









